

## KVM Switch Desktop 2 / 4 Port



### Features

- Complex connections with PCs via either way of PS/2 and/or USB arbitrarily
- Controls 2 / 4 computers from a single console PS/2 (Keyboard/Mouse) over PS/2 and/or USB connections
- Supports Windows, Linux, Mac OS9/OSX, Sun Microsystems
- Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error
- Supports hot-swap. All devices connected to the KVM can be added or removed at any time, without shutting the unit down
- Supports 2 types of switching:
  - (1) Hardware Push Button,
  - (2) Hot-Keys on PS/2 keyboard
- Supports Auto-Scan function to alternate video between computers in preset intervals
- Supports VGA resolutions up to 2048 x 1536 / 85HZ
- Supports Beeper during switching
- Self powered through PS/2 and/or USB connection using equip KVM Switch Cable Set (PS/2+USB)
- Fully compliant with the USB 1.1/ 2.0 specification



### Package Contents

- 2-Port or 4-Port Combo KVM Switch
- User Manual

Specification	331502	331504
Console Port: Keyboard	1x 6 pin mini-DIN female	
Console Port: Mouse	1x 6 pin mini-DIN female	
Console Port: Monitor	1x HDB 15 female	
PC Port (VGA, USB, PS/2 combined)	2x HDB 15 female	4x HDB 15 female
Max. VGA Resolution	2048 x 1536 / 85Hz	
DDC, DDC2 support	yes	
Hot Swappable	yes	
Auto Scan Interval	5 ~ 250 seconds	
Power	by PS/2 and/or USB port	
LED: PC selected	2 x red	4 x red
LED: PC on-line	2 x green	4 x green
Operation Temperature	0 ~ 50°C (32 ~122° F)	
Enclosure	Metal	
Dimensions (WxDxH)	140 x 80 x 45 mm	215 x 85 x 45 mm
Weight	420 g	625 g