

www.equip-info.net

Cat.6A Pro S/FTP Patch Cord



The equip® Cat.6A Pro S/FTP Patch Cord is composed of preeminent materials and fully-examined to conform with industrial standards. Offering higher bandwidth and better signal-to-noise margin, the Cat.7 cable is able to deliver ultrahigh and error-free performance in the most demanding network environments, specially for 10G application.

Key Feature

- 26AWG
- 500MHz
- Stranded
- PIMF (Pair In Metal Foil)

- Gold plated pins
- Molded boot
- Halogen free LSZH
- Cat.7 S/FTP Copper Raw Cable



www.equip-info.net

Specification

Conductor	Material	Bare Copper
	Construction	26AWG, 7/0.16 ± 0.005mm
Insulation	Thickness	MIN at any point: 0.2 mm / MAX AVG:0.35 mm
	Diameter	1.05 ± 0.05mm
	Colors	Blue-White/Blue,Orange-White/Orange,Green-White/Green, Brown-White/Brown
Jacket	Material	LSZH
	Thickness	MIN at any point: 0.50mm / MAX AVG: 0.60mm
	Diameter	6.2 ± 0.2mm

I Ordering Information

Length	Model No.
0.5m	605717
1.0m	605710
2.0m	605711
3.0m	605712
5.0m	605714
7.5m	605715
10.0m	605716
15.0m	605718
20.0m	605719

Packing: equip ZIP Bag

